



Commercial Building Solutions

LINE CARD



Leviton offers an extensive product line of commercial grade electrical, lighting, energy management and data networking devices. We are the trusted brand that provides safe, high quality products in many commercial buildings including several health care facilities, office buildings, hotels, universities and convention centers.

SAFE & RELIABLE INDUSTRIAL CONNECTIONS

OVER 115 YEARS IN THE INDUSTRY

Power Connectivity

STRAIGHT BLADE RECEPTACLES

Heavy-Duty Industrial Specification Grade Receptacles

- 15 and 20 Amp – 125 and 250 Volt
- Standard or Decora Plus™
- GFCI, Tamper-Resistant, Isolated Ground and Weather-Resistant versions available




Commercial Specification Grade Receptacles

- 15 and 20 Amp – 125 and 250 Volt
- Standard or Decora Plus™
- Tamper-Resistant and Marked "Controlled" versions available



USB Receptacles

- 15 and 20 Amp – 125 and 250 Volt
- Combined total of 5.1A charging current and 25+ watts of power
- Built-in overcurrent protection helps protect electronics from receiving too much power, which can damage the device



SWITCHES

Toggle and Decora Plus™ Switches

- 20 Amp - 120/277 Volt
- Pilot Light, Illuminated and Tamper-Resistant versions available



Antimicrobial Treated Switches & Wallplates

- 20 Amp - 120/277 Volt
- Toggle, Decora Plus™, Conventional Wiring or Lev-Lok®
- Helps to inhibit the growth of mold, mildew, fungi and odor-causing bacteria on the surface of switches and wallplates in between normal cleanings



WALLPLATES

Wallplates

- Available in Thermoplastic Nylon, Type 302 and 430 Stainless Steel, Aluminum and Brass
- Single and multi-gang configurations
- Antimicrobial Treated, Screwless and Gasketed versions available



LEV-LOK® MODULAR WIRING DEVICES

Lev-Lok Switches, Receptacles and Occupancy Sensors

- 3x faster installations and 5x faster swap outs than traditional wiring
- Traditional and Decora® Duplex, GFCI, Illuminated, MRI, USB, Marked Controlled Power Indication and Surge Protective Receptacles
- Single-Pole, Three-Way, Tamper-Resistant, Illuminated, and Antimicrobial Treated Switches
- Passive Infrared (PIR) and Multi-Technology (Ultrasonic and PIR) Occupancy Sensors*
- Mating Lev-Lok wiring module required for use



*Can be used to comply with ASHRAE 90.1, IECC and 2019 Title 24, Part 6 occupancy/vacancy sensing requirements

FLOOR BOXES

ALL ADA-COMPLIANT!

Poke-Through Floor Boxes

- Feature industry exclusive self-leveling feature, anchoring feature, and door-in-door cover design
- Available in Black, Gray, Nickel, and Brass finishes



Concrete Floor Boxes

- Round non-metallic floor box with a low voltage divider, concrete cover, and conduit reducers
- Can be used with finished floors made of wood, tile, vinyl, terrazzo, carpet and concrete
- Brushed Brass or Brushed Nickel finishes

Wood Frame Floor Boxes

- 15 and 20 Amp – 125 Volt
- Single and multi-gang configurations
- Brass or Nickel-Plated faceplates available



Pop-Up Floor Box Receptacles

- Pre-wired terminal block for easy wiring access and installation
- Low profile cover recesses to only ¼ inch when not in use
- Available in Brushed Nickel, Black, Brass, and Bronze finishes



Lighting Controls

WEATHERPROOF COVERS & BOXES

Weatherproof Device Covers & Boxes

- Available in 1-and 2-gang configurations
- Complies with the NEC® (2017) Section 406.9 for weatherproof enclosures in wet and damp locations
- Vertical or Horizontal Mounting



ELECTRICAL VEHICLE CHARGING

EV Series Charging Stations

- 32, 48 or 80 Amp
- Level 2: SAE J1772™ Compatible
- Restrict access with optional RFID
- Versions available compatible with the My Leviton app
- Available with 4G and management software capabilities
- For indoor and outdoor use, with a thermoplastic, water-resistant enclosure rated NEMA Type 3R



SURGE PROTECTION

Surge Protective Panels

- 120/208, 277/480 3-Phase Voltages
- Compliant with 2023 NEC requirement for emergency power systems



Surge Protective Receptacles

- 15 and 20 Amp - 125 Volt
- Single, Duplex and 4-in-1
- Point-of-use protection for up to 18,000 amps of surge current total
- Tamper-Resistant versions available



Measurement & Verification

SUBMETERING SOLUTIONS¹

VeriEye™ Meter Kits – Indoor & Outdoor

- 100 A - 5000 A, 120 V - 277/480 V
- Single Phase & Three Phase
- Isolated Pulse Output Standard
- NEMA 1 and 4X Enclosures
- Data collection hardware and BMO 3.0 energy information software available



OCCUPANCY SENSORS²

Decora® Wall Switch Multi-Technology Occupancy Sensors

- 120-277 V AC, 50/60Hz
- LED, Incandescent/Tungsten, Fluorescent
- UL and cUL Listed, ETL and cETL Listed



Ceiling-Mount Multi-Technology Occupancy Sensors

- Supports 24 V AC/DC power supplies
- Coverage Range: 500-2000 Sq. Ft.
- CUL/US, FCC and NOM Certified



Multi-Technology Wall or Corner Mount Occupancy Sensors

- Supports 24 V AC/DC power supplies
- Coverage: 1200 Sq. Ft.
- Adjustable swivel neck rotates 80° vertically and 60° horizontally
- CUL/US Certified



Fixture Mount PIR Sensors

- 120/277/347 V AC, 50/60Hz
- Indoor and outdoor models available
- IP65 models available
- Cold storage models available



RELAY PANELS²

GreenMAX®

- Cabinets with Short Circuit Current Rating (SCCR) of 25,000 A at 277 V AC
- Available in 8, 16, 32, or 48 relays
- Latching Relay Modules in 1-pole and 2-pole configurations
- LumaCAN and Ethernet network



EZ-MAX® Plus

- 120 V, 277 V and 347 V
- Available in 4 or 8 relays
- Standard 30 A Relay Card with Short Circuit Current Rating of 20,000 A



1 - Can be used to comply with ASHRAE 90.1 and 2019 Title 24, Part 6 service metering and disaggregation of electrical circuits requirements

2 - Can be used to comply with ASHRAE 90.1, and 2016 Title 24, Part 6 occupancy/vacancy sensing, 0-10V dimming, daylight harvesting, partial-ON, partial-OFF and demand response requirements

ROOM CONTROLS²

Provolt™ Room Controller (PRC) and App

- 120/277 V
- Self-contained device for occupancy sensing, 0-10 V dimming, daylight harvesting, partial-ON, partial-OFF, plug load control and demand response
- Configuration and control via the Provolt Bluetooth® mobile app
- Install with Provolt Keypad for manual control - 1, 2, or 4 button
- 1- or 2-zone control
- UL/cUL, CE, NOM, RoHS



Lumina™ RF Standalone Wireless Room Control System

- Delivers simple, scalable and flexible wireless control for any ON/OFF, 0-10V and phase cut dimming application
- Ideal for retrofits



2 - Can be used to comply with ASHRAE 90.1, and 2016 Title 24, Part 6 occupancy/vacancy sensing, 0-10V dimming, daylight harvesting, partial-ON, partial-OFF and demand response requirements

Integrated Room Control (IRC) Kit

- 120/277 V, 347 V
- Kit includes IRC, sensor, photocell and keypad for occupancy sensing, 0-10V dimming, daylight harvesting, partial-ON, partial-OFF and demand response
- Add OPP20 for plug load control
- 2- or 3-zone control
- UL/cUL Listed



Decora® Slide Dimmers

- For any type of load including LED and 0-10V
- Separate ON/OFF rocker switch allows you to set and keep preferred dimming level



IlumaTech® Dimmers

- For any type of load including LED and 0-10V
- Push button on/off preserves the selected brightness setting



SureSlide® Dimmers

- Integrated linear full range slide control for easy, precise operation
- Preset versions feature a separate on/off switch that preserves the selected brightness setting



Data Centers & Networking

NETWORK SOLUTIONS

Atlas-X1™ System

- Highest level of verified performance
- Supports high-bandwidth wireless networks
- Tool-free termination for fast deployment



Quickport® and 110-Style Patch Panels

- Industry's largest selection of patch panels
- Configurations for unique applications
- Multitude of port densities to support high-speed data applications



Opt-X® Unity Fiber Cabling System

- Premium fiber cabling system
- Reuse fiber backbone for migrations from 10 to 40, 100 and 400 Gb/s
- Ultra low loss connectivity allows longer distances and multiple connection points



IT/AV Control System

- Connects up to three sources to a single display
- No programming or user training required
- HDBaseT™-certified for product compatibility



Visit our Website at:

leviton.com/commercialbuildings

email: commercial@leviton.com

Leviton Manufacturing Co., Inc.

201 N Service Rd, Melville, NY 11747

Telephone: 1-800-323-8920 • FAX: 1-800-832-9538

Tech Line: 1-800-824-3005 (M-F 8AM-10PM; Sat 9AM-7PM; Sun 9AM-5PM)

© 2024 Leviton Manufacturing Co., Inc. All rights reserved.

Q-1132C